

30 kW Load Bank



30KW LOAD BANK:

Ruggedized

Evaluates Generator Efficiency

Prevents Wet-Stacking

Optimized for Compatibility with
PDISE

Specifically Designed for Military
Applications

Fidelity's 30kW load bank is an ideal rugged option to test and maintain Tactical Quiet Generators in the field. Designed to meet MIL-STD-810 and MIL-STD-705, Fidelity's 30kW Load Bank is designed to endure harsh environmental conditions.

FEATURES

- INCLUDES 15', 100 AMP PIGTAIL
- RESISTIVE LOAD
 - LOAD STEPS: 1kW, 2kW, 2kW, 5kW, 10kW, 10kW @ 208VAC
 - LOAD STEPS: .66kW, 1.33kW, 1.33kW, 3.33kW, 6.66kW, 6.66kW @ 240VAC
 - LOAD STEPS: .33kW, .66kW, .66kW, 1.66kW, 3.33kW, 3.33kW @ 120VAC
- INPUT POWER: 208VAC, 3PHASE, 240VAC, SINGLE PHASE, 120VAC, SINGLE PHASE
- CLASS D MILITARY STYLE CONNECTOR
- OPERATING TEMPERATURE: -25C TO 55C (-13F TO 131F)
- STORAGE TEMPERATURE: -25C TO 71C (-13F TO 160F)
- CARC FINISH (OLIVE DRAB)
- WEIGHT: ~50 LBS
- DIMENSIONS: 24.5"LX14.25"WX18.5"H (WITHOUT 4.5" CONNECTOR)
- SAFETY FEATURES:
 - OVERVOLTAGE SENSE
 - TEMPERATURE SENSE
 - AIRFLOW SENSE
 - OVERCURRENT FUSES
- DESIGNED FOR MILITARY ENVIRONMENT (MIL-STD-810 AND MIL-STD-705):
 - SAND AND DUST
 - CORROSION
 - FUNGUS
 - SHOCK
 - VIBRATION
 - MILITARY CONNECTORS

FIDELITY
TECHNOLOGIES
CORPORATION

Simulation and Training ■ Field Services ■ Military and Aerospace Manufacturing

2501 Kutztown Road, Reading, PA 19605
(p) 610.929.3330 800.743.5492 (f) 610.929.1969 www.fidelitytech.com